

DILUCO™ SU-1505

Features & Benefits

- Ready to use
- Non Staining Synthetic Lubricant
- Will not interfere with painting or plating
- No Buildup
- Excellent Firm Formation



PACKAGING:

Totes
Drums
Pails
32oz Spray Bottle



DILUCO™ SU-1505 is a high performance, petroleum based lubricant developed for use on die surfaces during the start-up phase of operation. The chemically balanced, ready-to-use blend of natural lubricants, unique polymers and severely hydro-treated oils, provide an excellent release film to the die surface and lubricates ejector pins, slides, fins and core areas under lower than normal die temperatures.

TYPICAL CHARACTERISTICS:

Color	Amber
Odor	Pleasant
Density (lbs./gal)	7.1
Water Solubility	Non-dispersible

APPLICATION:

This product is designed to be used as is and not diluted. Used with a spray bottle applied to the mold surface.

HANDLING & STORAGE:

Containers:	5gal (18 liters), 55gal (207 liters) and tote quantities available.
Shelf Life:	1 year under original seal, unopened containers.
Disposal:	Dispose of product appropriately, following all federal, state, and local regulations.
Freezing:	Do not freeze. If frozen, thaw to room temperature by first gentle warming to room temperature and then thoroughly mixing the concentrate product before use.

HEALTH & SAFETY:

Refer to the product Safety Data Sheet (SDS).