

Plunger™Lube 279

Performance Benefits

- Excellent Lubrication under extreme pressure
- Suitable for Aluminum, Zinc or Magnesium
- Excellent Wetting
- No Stain-Outstanding Cosmetics
- Prolonged Tip & Sleeve Life



Plunger Shot™ 279 is a high-performance lubricant, specifically formulated for the lubrication of shot tips and sleeves.

This product contains a blend of unique polymers and wetting agents that adhere to the tip and remains on the surface under extreme high pressure.

TYPICAL CHARACTERISTICS

FORM:	Solid
APPEARANCE:	White
ODOR:	Bland
FLASHPOINT:	> 250° F
SIZE:	1.0 – 1.5 mm

RECOMMENDED AMOUNTS

It is recommended to use 1 gram per inch diameter of the tip.

DIAMETER OF TIP	AMOUNT OF BEADS
2 INCH	2 GRAMS
3 INCH	3 GRAMS
4 INCH	4 GRAMS

*Note excess amounts should be avoided due to the potentials for porosity.



2.2

HEALTH & SAFETY

All reasonable care has been taken to ensure that the information contained in this publication is accurate as the date of printing, however, such information might change due to changes in the formulation blend occurring subsequent to the date of printing. The MSDS must be consulted for appropriate information regarding storage, safe handling and storage.